



UJ physical dimensions

part number													
type (OC, OI, etc.)	outer diameter, in 16ths of an inch	placeholder, D	bore one size, in 16ths of an inch (E) or in mm (M)	E = English, M = metric bore	bore one type (b = blind, T = thru, K = keyway)	bore two size, in 16ths of an inch (E) or in mm (M)	E = English, M = metric bore	bore two type (b = blind, T = thru, K = keyway)	S = set screw, C = clamping	hub material (see chart at right)	placeholder, "HUB"	midsection material (see chart at right)	placeholder, "MID"
UJ	4	D	2	M	B	2	M	B	S	A	HUB	F	MID
UJ	6	D	2	M	B	3	M	B	S	S	HUB	F	MID
UJ	8	D	2	M	B	4	M	B	S	A	HUB	F	MID
UJ	10	D	6	M	B	4	M	B	C	A	HUB	F	MID
UJ	12	D	4	M	B	4	M	B	C	B	HUB	F	MID
UJ	14	D	4	M	B	4	M	B	C	B	HUB	F	MID
UJ	16	D	6	M	B	6	M	B	S	A	HUB	F	MID
UJ	21	D	8	M	B	8	M	B	S	S	HUB	F	MID
UJ	26	D	8	M	B	8	M	B	C	A	HUB	F	MID
UJ	32	D	8	M	B	10	M	B	C	A	HUB	F	MID
UJ	36	D	8	M	B	10	M	B	S	A	HUB	F	MID

physical dimensions, inches						
A	B	C, min	D, min	E	min bore for this OD	max bore for this OD
0.71	0.25	0.188	0.188	0.334	0.079	0.125
1.1	0.375	0.306	0.306	0.488	0.118	0.197
2	0.5	0.68	0.68	0.64	0.118	0.25
2.25	0.625	0.729	0.729	0.792	0.125	0.315
2.69	0.75	0.873	0.873	0.944	0.157	0.313
3	0.875	0.947	0.947	1.106	0.196	0.4375
3.38	1	1.066	1.066	1.248	0.236	0.472
3.75	1.3125	1.064	1.064	1.622	0.25	0.63
4.25	1.625	1.118	1.118	2.014	0.25	0.787
5.44	2	1.485	1.485	2.47	0.25	1
6	2.25	1.609	1.609	2.782	0.25	1.181